



MODEL / SPEC.	A	B	C	D	E	F	G	H	I	J	K	L
RT-05	136	85	16	60	6	180	33	62	14	10	25	6-M8×1.25P
RT-06	166	93	20	80	7	210	40	73	20	12	31	6-M8×1.25P
RT-08	215	112	30	110	8	250	42	95	25	14	35	6-M10×1.5P
RT-10	255	120	43	140	8	290	46	110	30	16	40	6-M10×1.5P
RT-05T	136	85	16	60	6	180	33	62	14	10	25	6-M8×1.25P
RT-06T	166	93	20	80	7	210	40	73	20	12	31	6-M8×1.25P

MODEL / SPEC.	M	P	Thru-Hole	Piston Area	Plunger	Jaw Stroke
			(Diameter) mm			
RT-05	Ø118	27	16	74	10	4.6
RT-06	Ø147	27	20	120	13	5.5
RT-08	Ø185	28	30	190	16	6.8
RT-10	Ø220	30.5	43	280	19	8
RT-05T	Ø118	27	16	74	10	4.6
RT-06T	Ø147	27	20	120	13	5.5

MODEL / SPEC.	Max. Speed	Max. Pressure	Gripping Force	Gripping	Weight
	rpm	kgf/cm <sup>2</sup>	kgf (KN)	Range	kg.
RT-05	51	7 (0.7)	1340 (13.1)	Ø4-Ø136	9.3
RT-06	41	7 (0.7)	2330 (22.8)	Ø25-Ø166	15.5
RT-08	33	7 (0.7)	3730 (36.5)	Ø33-Ø215	28.5
RT-10	26	7 (0.7)	5480 (53.7)	Ø43-Ø255	42.3
RT-05T	51	7 (0.7)	1340 (13.1)	Ø4-Ø136	
RT-06T	41	7 (0.7)	2330 (22.8)	Ø25-Ø166	